

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: JCUP1598:CRYSTAL URK1743 YELLOW 4x1L
Product code	: JCUP1598
Trade name	: GCC UV CURABLE INK UV YELLOW INK
Index number	:

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Colorant; Printing ink related material; Printing ink.		
Uses advised against	Reason	

1.3 Details of the supplier of the safety data sheet

Manufacturer/ Distributor	: SUNJET NORTON HILL MIDSOMER NORTON BATH SOMERSET BA3 4RT UNITED KINGDOM (44) 1761 414471 SUNJET NORTON HILL MIDSOMER NORTON BATH SOMERSET BA3 4RT UNITED KINGDOM (44) 1761 414471
e-mail address of person responsible for this SDS	: regulatory.affairs@sunchemical.com
1.4 Emergency telephone nu Supplier	nber
Telephone number	: (44) 870-8200418 (Chemtrec - 24 hours) (1)703 527 3887(Chemtrec International-24 hours)

....

. ...

....

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Repr. 2, H361f STOT RE 1, H372 Aquatic Chronic 2, H411

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	T; R48/23 Xi; R36/37/38 R43 N; R51/53
Human health hazards	Toxic: danger of serious damage to health by prolonged exposure through inhalation. Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.
Environmental hazards	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
See Section 16 for the full te	the R-phrases declared above

See Section 16 for the full text of the R-phrases declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility. Causes damage to organs through prolonged or repeated exposure if inhaled. (liver) Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Obtain special instructions before use. Do not eat, drink or smoke when using this product.
Response	: IF exposed or concerned: Get medical attention. IF IN EYES: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	 * vinylhexahydro-2H-azepin-2-one (5-ethyl-1,3-dioxan-5-yl)methyl acrylate diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide
Supplemental label elements	: Not applicable.

2.3 Other hazards

Date of issue

SECTION 2: Hazards identification

Other hazards which do
not result in classification: None known.

SECTION 3: Composition/information on ingredients

<u>Classification</u>		ification			
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
rvinylhexahydro-2H- azepin-2-one	REACH #: 01-2119977109-27 EC: 218-787-6 CAS: 2235-00-9	20 < 25	T; R48/23 Xn; R22 Xi; R36 R43	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372	[1]
2-phenoxyethyl acrylate	EC: 256-360-6 CAS: 48145-04-6	20 < 25	R43 N; R51/53	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
(5-ethyl-1,3-dioxan- 5-yl)methyl acrylate	EC: 266-380-7 CAS: 66492-51-1	20 < 25	Xi; R38 R43 N; R51/53	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
monoalkyl or monoaryl or monoalkylaryl esters of acrylic acid	EC: 227-561-6 CAS: 5888-33-5 Index: 607-133-00-9	10 < 20	Xi; R36/37/38 N; R51/53	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
diphenyl(2,4, 6-trimethylbenzoyl) phosphine oxide	EC: 278-355-8 CAS: 75980-60-8	2.5 < 5	Repr. Cat. 3; R62 N; R51/53	Repr. 2, H361f Aquatic Chronic 2, H411	[1]
phenyl bis(2,4, 6-trimethylbenzoyl)- phosphine oxide	EC: 423-340-5 CAS: 162881-26-7	2.5 < 5	R43 R53	Skin Sens. 1A, H317 Aquatic Chronic 4, H413	[1]
Epoxy Acrylate Oligomer	Index: 015-189-00-5 CAS: PROPRIETARY	1.0 < 2.5	Xi; R36/38	Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
trimethylolpropane triacrylate	REACH #: 01-2119489896-11 EC: 239-701-3 CAS: 15625-89-5 Index: 607-111-00-9	1.0 < 2.5	Xi; R36/38 R43 R52/53	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
Stabiliser A	CAS: Proprietary	0.1 < 0.25	N; R50/53	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1]
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

SECTION 3: Composition/information on ingredients

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid m	neasures
General	 In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with room temperature water for at least 15 minutes, keeping eyelids open. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion may cause nausea, weakness and central nervous system effects.

Contains 1-vinylhexahydro-2H-azepin-2-one, 2-phenoxyethyl acrylate, (5-ethyl-1,3-dioxan-5-yl)methyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, trimethylolpropane triacrylate, Glycerol Propoxy Triacrylate . May produce an allergic reaction.

The following products have sensitizing properties: 1-vinylhexahydro-2H-azepin-2-one, 2-phenoxyethyl acrylate, (5-ethyl-1,3-dioxan-5-yl)methyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, trimethylolpropane triacrylate, Glycerol Propoxy Triacrylate

. Cases of hypersensitivity may occur, possibly with cross-sensitization to other acrylate materials.

4.3 Indication of any immediate medical attention and special treatment needed

Date of issue	: 10 August, 2015
---------------	-------------------

Notes to medical doctor	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures	
----------------------------------	--

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous thermal	: Decomposition products may include the following materials: carbon monoxide,

decomposition products	carbon dioxide, smoke	, oxides of nitrogen.	C C

5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	: Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel		Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.		
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.		
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.		

SECTION 7: Handling and storage

Persons with a history of skin sensitization problems should not be employed in any process in which this product is used, without Personal Protective Equipment measures.

7.1 Precautions for safe handling	 Use only in well-ventilated areas. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Keep container tightly closed. Keep away from heat, sparks and flame. Always keep in containers made from the same material as the original one. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Comply with the health and safety at work laws.
7.2 Conditions for safe	: Store between the following temperatures: 5 - 35 °C
storage, including any incompatibilities	Keep away from heat and direct sunlight.
	Store in accordance with local regulations.
	Notes on joint storage
	Keep away from: oxidizing agents, strong alkalis, strong acids.
	Additional information on storage conditions
	Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.
	Keep container tightly closed.
	Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep only in the original container.
	Keep away from heat and direct sunlight.
7.3 Specific end use(s)	
Recommendations	Not available.
Industrial sector specific	Not available.
solutions	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs/DMELs	

Date of issue

SECTION 8: Exposure controls/personal protection Product/ Type Exposure Value Population Effects ingredient name No DELs available. **PNECs** Product/ingredient name Value Method Detail **Compartment Detail** Type No PECs available. 8.2 Exposure controls Appropriate engineering : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If controls these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn. Individual protection measures Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eve/face protection : Use safety evewear designed to protect against splash of liquids. Skin protection : Barrier creams may help to protect the exposed areas of the skin but should not be Hand protection applied once exposure has occurred. Gloves : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be

		different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	"RadTech recommend use of: -single use: disposable, unpowdered, nitrile gloves: Use for short duration exposures not exceeding 30 minutes, in situations where only splashes are likely. Do not use where mechanical resistance is required or where puncturing or tearing of the gloves is likely to occur. Replace immediately if punctured, degraded or tearing of the gloves has occurred. -general use: minimum 0.45mm thick, unlined, unpowdered, natural rubber latex- free nitrile gloves: Use for longer duration exposure (up to 4 hours for most UV/EB curing acrylates) or mechanical handling activities. Replace immediately when punctured or when a change of appearance (colour, elasticity, shape) occurs - heavy duty: unlined, natural rubber latex-free nitrile gloves: Use when handling solvents. Avoid the use of chlorinated solvents and limit the use of ketones (e.g. acetone, MEK, MIBK) and ethyl and butyl acetates, as they may accelerate glove deterioration."
Body protection	:	Personnel should wear protective clothing.
Respiratory protection	:	In situations where misting or flying may occur, use appropriate certified respirators.
Environmental exposure	:	Do not allow to enter drains or watercourses.

Environmental exposure controls

SECTION 9: Physical and chemical properties

9.1 Information on basic physic	al and chemical properties
Physical state	: Liquid.
Color	: Yellow.
Odor	: Characteristic.
Odor threshold	: Not applicable.
Melting point/freezing point	: Not applicable.
Flash point	: 96°C
VOC	: 0%
рН	: Not tested
Boiling point	: Lowest known value: 132°C (270°F)
Evaporation rate	: <1 (trimethylolpropane triacrylate) compared with butyl acetate
Upper/lower flammability or explosive limits	: Not tested

Upper/lower flammability or explosive limits	: Not tested	
Vapor pressure	: Not tested	
Vapor density	: Not tested	
Relative density	: Not tested	
Solubility(ies)	: Not tested	
Partition coefficient: n-octanol/ water	: Not applicable.	
Auto-ignition temperature	: Not applicable.	
Decomposition temperature	: Not applicable.	
Viscosity	: Not tested	
Explosive properties	: Not applicable.	
Oxidizing properties	: Not applicable.	

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients	5.
10.2 Chemical stability	: Hazardous reactions or instability may occur under certain conditions of storage o use.	r
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: This mixture contains materials which are unstable under the following conditions: exposure to heat, strong UV sources. These could cause the product to polymeriz exothermically. Unintentional contact with them should be avoided.	
10.5 Incompatible materials	: Keep away from: free radical initiators, peroxides, strong alkalis, reactive metals.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

Date of issue	: 10 August, 2015	Page: 8/14
---------------	-------------------	------------

SECTION 10: Stability and reactivity

Hazardous polymerization : May polymerize on exposure to sunlight.

SECTION 11: Toxicological information

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion may cause nausea, weakness and central nervous system effects.

Contains 1-vinylhexahydro-2H-azepin-2-one, 2-phenoxyethyl acrylate, (5-ethyl-1,3-dioxan-5-yl)methyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, trimethylolpropane triacrylate, Glycerol Propoxy Triacrylate . May produce an allergic reaction.

The following products have sensitizing properties: 1-vinylhexahydro-2H-azepin-2-one, 2-phenoxyethyl acrylate, (5-ethyl-1,3-dioxan-5-yl)methyl acrylate, phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide, trimethylolpropane triacrylate, Glycerol Propoxy Triacrylate

. Cases of hypersensitivity may occur, possibly with cross-sensitization to other acrylate materials.

11.1 Information on toxicological effects

 Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
1-vinylhexahydro-2H-azepin- 2-one	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-
monoalkyl or monoaryl or monoalkylaryl esters of acrylic acid	LD50 Dermal	Rabbit	>5 g/kg	-
-	LD50 Oral	Rat	4890 mg/kg	-
trimethylolpropane triacrylate	LD50 Dermal	Rabbit	5170 mg/kg	-

Irritation/Corrosion

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

<u>Sensitization</u>

Acute toxicity

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Mutagenicity

Not applicable.

Carcinogenicity

Not applicable.

Reproductive toxicity

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/ GHS]

Teratogenicity

Not applicable.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

12.1 Toxicity

Not available.

12.2 Persistence and degradability

Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
diphenyl(2,4, 6-trimethylbenzoyl)	-	53 to 72	low
phosphine oxide phenyl bis(2,4, 6-trimethylbenzoyl)-	5.77	-	high
phosphine oxide trimethylolpropane triacrylate	0.67	-	low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.
12.5 Results of PBT and	vPvB assessment
PBT	: Not applicable.

FDI	. Not applicable.
vPvB	: Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

13.1 Waste treatment methods

<u>Product</u>		
M - 411 -		

Methods of disposal: The generation of waste should be avoided or minimized wherever possible.
Disposal of this product, solutions and any by-products should at all times comply
with the requirements of environmental protection and waste disposal legislation
and any regional local authority requirements. Dispose of surplus and non-
recyclable products via a licensed waste disposal contractor. Waste should not be
disposed of untreated to the sewer unless fully compliant with the requirements of
all authorities with jurisdiction.

Packaging

Date of issue

SECTION 13: Disposal considerations Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. European Waste Catalogue (EWC): : 08 03 12 waste ink containing dangerous substances Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of

spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-propenoic acid, 2-phenoxyethyl ester; 2-Propenoic Acid, (5-ethyl-1,3-dioxan- 5-yl)methyl ester)			
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	111	111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional information	-	-	-	-

14.6 Special
precautions for
userTransport within user's premises: always transport in closed containers that are upright and
secure. Ensure that persons transporting the product know what to do in the event of an
accident or spillage.

14.7 Transport in bulk: Not available.according to Annex II ofMARPOL 73/78 and the IBCCode

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
diphenyl(2,4, 6-trimethylbenzoyl) phosphine oxide	-	-	-	Repr. 2, H361f
Industrial use	own assessment of legislation. The pro	The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.		
15.2 Chemical Safety Assessment	This product contation to be received.	ains substances for wh	nich Chemical Safety A	ssessments are still

SECTION 16: Other information

Date of issue	: 10 August, 2015 Page:	12/14	
	H411 Toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.		
	H410 Very toxic to aquatic life with long lasting effects.		
	H400 Very toxic to aquatic life.		
	inhaled.		
	H372 Causes damage to organs through prolonged or repeated exposure if		
	H361f Suspected of damaging fertility.		
	H335 May cause respiratory irritation.		
	H319 Causes serious eye irritation.		
	H315 Causes skin irritation. H317 May cause an allergic skin reaction.		
statements	H312 Harmful in contact with skin.		
Full text of abbreviated H	: H302 Harmful if swallowed.		
	RRN = REACH Registration Number		
	PNEC = Predicted No Effect Concentration		
	EUH statement = CLP-specific Hazard statement		
	DNEL = Derived No Effect Level		
	1272/2008]		
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.		
Abbreviations and	: ATE = Acute Toxicity Estimate		
Indicates information that	has changed from previously issued version.		
CEPE code	: 4		

SECTION 16: Other information

	H413 May cause long lasting harmful effects to aquatic life.	
Full text of classifications [CLP/GHS]	 Kcute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H410 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Aquatic Chronic 4, H413 Aquatic Chronic 4, H413 Aquatic Chronic 4, H413 Aquatic Chronic 4, H413 AQUATIC HAZARD (LONG-TERM) - Category 2 Aquatic Chronic 4, H413 AQUATIC HAZARD (LONG-TERM) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Toxic To REPRODUCTION [Fertility] - Category 2 Skin Sens. 1, H317 Skin Sens. 1A, H317 Skin Sens. 1A, H317 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): INHALATION [liver] - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Respiratory tract irritation] - Category 3 	
Full text of abbreviated R	: R62- Possible risk of impaired fertility.	
phrases	 R48/23- Toxic: danger of serious damage to health by prolonged exposure through inhalation. R22- Harmful if swallowed. R36- Irritating to eyes. R38- Irritating to skin. R36/38- Irritating to eyes and skin. R36/37/38- Irritating to eyes, respiratory system and skin. R43- May cause sensitization by skin contact. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 	
Full text of classifications [DSD/DPD]	: Repr. Cat. 3 - Toxic to reproduction category 3 T - Toxic Xn - Harmful Xi - Irritant N - Dangerous for the environment	
Date of printing	: 10/20/2015.	
Date of issue/ Date of revision	: 8/10/2015.	
Date of previous issue	: 11/20/2014.	
Version	: 1	
Notico to roador		

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Annex