

TECHNICAL DATA SHEET Process Colour CMYK Resin Ribbon CPM-100

This technical data refers to the following Lighthouse products:

DESCRIPTION

Offering vibrant process colour printing to on Lighthouse Premium grade vinyl and Ultrabond materials. Outdoor durable and highly scratch, rub and oil resistant.

TECHNICAL DATA

TECHNICAL DATA		
Thickness Ink coat weight	1.05 ±0.3 g/m ² 1.10 ±0.3 g/m ² 1.05 ±0.3 g/m ² 1.25 ±0.3 g/m ²	CPMR53 CPMR54 CPMR55 CPMR56
Base film thickness	4.5µ ±0.4µ	
Storage	1 year Stored at 15 to 25°C and ±50% relative humidity. Avoid temperatures above 40°C and below 0°C	
Compliance	RoHS REACH	

IMPORTANT NOTICE

All Lighthouse products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects.

Published information concerning Lighthouse products is based on research, which the Company believes to be reliable, although such information does not constitute a warranty.

Because of the variety of uses of Lighthouse products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use. We recommend the purchaser conducts their own testing to determine the suitability for their required application. The purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.



